



圆底消防桶
ROUND BOTTOM FIRE BUCKETS

- ▶ 容量: 20升 / Capacity: 20L
- ▶ 材料: 钢 / Material: steel
- ▶ 表面处理: 红色环氧涂层
Surface treatment: red epoxy coating

砂箱

SANDBOX

- 容量: 200升 / Capacity: 200L
- 材料: 钢 / Material: steel
- 表面处理: 聚酯纤维涂层
Surface treatment: polyester coating



卷盘固定支架

FIXED SUPPORT FOR HOSE REELS

- ▶ 材料: 钢 / Material: steel
- ▶ 表面处理: 聚酯纤维涂层
Surface treatment: polyester coating



消防卷盘工具箱

CONTROL KIT FOR HOSE REELS

消防卷盘工具箱包括: 1个DN20-65接口扳手, 1个DN25消防卷盘压力表, 压力范围: 0-16公斤, 1个DN33消防卷盘压力表, 压力范围: 0-16公斤。

Control kit contains a spanner wrench for couplings DN20 to 65, inspection fitting for hose reels DN25 with manometer 0-230 PSI, inspection fitting for hose reels DN33 with manometer 0-230 PSI



泡沫消防卷盘 - 中倍数 & 低倍数

FOAM ADAPTATION KIT FOR HOSE REEL - MEDIUM & LOW EXPANSION

- ▶ 额定压力: PN16 / Nominal pressure: PN16

泡沫枪 / Nozzle:

- ▶ 材料: 铝合金和不锈钢 / Material: aluminium alloy and stainless steel
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 开关阀门类型: 球阀 / Shutoff: with ball valve
- ▶ 开关: 操作杆或手柄 / Opening: by lever or operating handle
- ▶ 发泡倍数: 约 70倍 或 10倍 / Foam expansion: x70 or x10

泡沫比例混合器 / Eductor:

- ▶ 材料: 铝合金 / Material: aluminium alloy
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 混合比: 1, 2, 3, 4, 5 和 6% / Suction percentage: 1,2,3,4,5 and 6%
- ▶ 止回阀 / Non-return valve

- ▶ 配吸液软管 / Delivered with suction hose



卷盘防尘罩

COVER FOR HOSE REELS

博克卷盘防尘罩适用与固定式卷盘或摆动式卷盘。
防尘罩采用防水布可有效防尘防垢。
根据卷盘直径, 防尘罩有两种尺寸可选。

Our cover is compatible with fixed and rotating hose reels.
This coated canvas cover protects the installation from dust and dirt.
It is available in 2 different sizes, depending on the hose reel size.

材料: 聚酯包覆PVC / Material: polyester PVC coated



接口*

COUPLINGS*

*根据您的需要, 产品可配不同类型的接口

*Products can be equipped with different types of couplings if needed



STORZ NST GFR MACHINO GOST DSP BARCELONA INSTANTANEOUS

01127_Flyer CH-EN_建筑业_building industry



POK CHINA

博克消防装备科技有限公司

地址: 北京市顺义区南彩镇彩达三街一号茂华工场5号厂房2层201室 · POK

电话: 010 64667868

邮箱: info@pokchina.com sales@pokchina.com

www.pokchina.com

建筑业
BUILDING INDUSTRY



激情的创造者 / WE CREATE WITH PASSION

消防卷盘 HOSE REELS

旋转 - 摆动 - 带软管和喷头 - DN33 Rotating - Swinging - With hose and diffuser - DN33

- ▶ 最大工作压力: 100PSI / Max. working pressure: 100 PSI
- ▶ 材料: 钢和铝合金 / Material: steel and aluminium alloy
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 开关: 手轮式阀门 / Shutoff: with handwheel shutoff
- ▶ 选配: 地面固定柱 · 消防栓箱 · 防尘罩
Options: mounting support, cabinet, cover



In compliance with norm
EN 671-1

旋转 - 摆动 - 带软管和喷头 - DN19, DN25 Rotating - Swinging - With hose and diffuser - DN19, DN25

- ▶ 最大工作压力: 170PSI / Max. working pressure: 170 PSI
- ▶ 材料: 钢和铝合金 / Material: steel and aluminium alloy
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 开关: 球阀 / Shutoff: with ball valve
- ▶ 选配: 地面固定柱 · 消防栓箱 · 防尘罩
Options: mounting support, cabinet, cover



泡沫消防卷盘 HOSE REEL WITH FOAM EXTENSION

泡沫消防卷盘, 中低倍数 Foam hose reel, medium and low expansion

- ▶ 额定压力: PN16 / Nominal pressure: PN16
- ▶ 消防卷盘 / Hose reel:
 - ▶ 材料: 钢和铝合金 / Material: steel and aluminium alloy
 - ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
 - ▶ 开关: 手轮式阀门 / Shutoff: with handwheel shutoff
- ▶ 泡沫枪 / Nozzle:
 - ▶ 材料: 铝合金 / Material: aluminium alloy
 - ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
 - ▶ 开关类型: 球阀 / Shutoff: with ball valve
 - ▶ 开关: 通过手柄 / Opening: by lever
 - ▶ 发泡倍数: 约70倍或10倍 / Foam expansion: x70 or x10
 - ▶ 泡沫枪带提取手柄 / Nozzle with carrying handle
- ▶ 泡沫比例混合器 / Eductor:
 - ▶ 材料: 铝合金 / Material: aluminium alloy
 - ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
 - ▶ 混合比: 1, 2, 3, 4, 5 和 6% / Suction percentage: 1,2,3,4,5 and 6%
 - ▶ 止回阀 / Non-return valve
 - ▶ 配吸液软管 / Delivered with suction hose



湿式消防栓 OUTLET WET STANDPIPES

双出口湿式消防栓 Double outlet wet standpipes

- ▶ 额定压力: PN16 / Nominal pressure: PN16
- ▶ 阀门类型: 止回阀 / Valve type: clapped
- ▶ 材料: 铜 / Material: bronze
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 开关: 手轮 / Shutoff: by handwheel


单出口湿式消防栓 One outlet wet standpipes

- ▶ 额定压力: PN16 / Nominal pressure: PN16
- ▶ 阀门类型: 止回阀 / Valve type: clapped
- ▶ 材料: 铜 / Material: bronze
- ▶ 表面处理: 聚酯纤维涂层 / Surface treatment: polyester coating
- ▶ 开关: 手轮 / Shutoff: by handwheel



- ▶ 闷盖带链条或不锈钢绳 / Caps with locking ring and chain or stainless steel wire
- ▶ 材料: 青铜 / Material: bronze

In compliance with norm
EN 671-1




流量计 FLOWMETER

- ▶ 构成: 铝合金和合成材料
Construction: aluminium alloy and composite
- ▶ 表面处理: 硬质阳极氧化 / Surface treatment: hard anodization
- ▶ 额定压力: PN16 / Nominal pressure: PN16
- ▶ 测量流量, 压力和体积 / Measurement of flow, pressure and volume
- ▶ 防水: IP65 / Waterproofness: IP65
- ▶ 精确度: 3% / Accuracy: 3%
- ▶ 流量读取单位: 升/分 或 加仑/分 (工厂设定)
Flow display: L/min or GPM (factory settings)
- ▶ 压力读取单位: 公斤或磅/平方英寸 (工厂设定)
Pressure: bar or PSI (factory settings)
- ▶ 电源: 可充电锂电池
Power supply: rechargeable battery Li-ion
- ▶ 续航时间: 可达 40小时 / Self-efficiency: up to 40 hours



不锈钢消防软管卷盘 HOSE REELS, SWINGING ROTATING IN STAINLESS STEEL

- ▶ DN25 - 最大工作压力: 12 公斤
Max. working pressure: 170 PSI
- ▶ DN33 - 最大工作压力: 7 公斤
Max. working pressure: 100 PSI
- ▶ 软管: DN 25 或 DN 33 / Hose: DN 25 or DN 33
- ▶ 软管长度: 30 米 / Hose capacity: 30 meters
- ▶ 选配: 固定支架 / Option: fixed support



不锈钢消防软管卷盘 HOSE REELS, SWINGING ROTATING IN STAINLESS STEEL

- ▶ 最大工作压力: 12 公斤
Max. working pressure: 170 PSI
- ▶ 开关: 手轮式开关阀 / Shutoff: with handwheel shutoff
- ▶ 软管: DN 25 / Hose: DN 25
- ▶ 软管长度: 30 mètres / Hose capacity: 30 meters
- ▶ 选配: 固定支架 / Option: fixed support



带支架消防卷盘 HOSE REEL ON SUPPORT

- ▶ 卷盘带软管和喷头 - DN25 或 DN33
Hose reel with hose and diffuser - DN25 or DN33
- ▶ DN25 - 最大工作压力: 12 公斤 / Max. working pressure: 170 PSI
- ▶ DN33 - 最大工作压力: 7 公斤 / Max. working pressure: 100 PSI
- ▶ 材料: 不锈钢 / Material: stainless steel
- ▶ 三档位黄铜喷头: 关, 喷雾和直流
Diffuser in brass, 3 positions: closed, wide spray angle and straight jet

